

Standard Equipment

- ✓ Single-phase 230V/50Hz electric motor
- ✓ Gearmotor with steel and technopolymer gears
- ✓ Available in the versions with steel drum and poly drum (HDPE)
 - Electric safety: built to EN 60204-1 double insulation norms,
- ✓ protected against spraying water (IP 55) and against overload and inadvertent starting again after a power failure.
- ✓ Packing: cardboard

Optional Accessory

- ✓ Rotating pivoting support

| | |
|------------------------|----------------------|
| 115V/60Hz SPH | 220V/60Hz SPH |
| MOTOR AVAILABLE | |
| ✓ Rollbeta | |

Applications

It is the lightweight, compact concrete mixer easy to transport, ideal for small building sites or refurbishment work. Its construction features make it suitable for professional use.



ROLLBETA
with **STANDARD DOUBLE INSULATION**
in accordance with Std. EN12151



Rotating pivoting support (optional)

ROLLBETA

| | | |
|----------------------------|-------|--------------|
| Drum capacity | l | 138 |
| Batch output | l | ~100 |
| Drum diameter | mm | 610 |
| Wheel dimensions | Ø mm | 370x60 |
| Motor power rate | kW | 0.3 |
| Running current | A | 2.3 |
| SPL in operator's position | dB(A) | 63 |
| Machine weight | kg | 46 |
| Machine dim. w/l/h | mm | 660/1170/920 |
| Packing dim. w/l/h | mm | 660/730/700 |